ARMORVUE® WINDOW & DOOR
POWERED BY WINDOW NATION

Single-hung window

MODEL: 3540 - PerformanceView

Boasting a stylish look, the 3540 single-hung window is specifically designed to meet high design pressure (DP) requirements for remodeling and replacement projects. The removable meeting rail, sash, and top-glass allow for easy drywall pass-through while multiple color options, stylish beveled profile, full-length lift rail, and metal reinforcements at the meeting rail provide homeowners with aesthetic options and desirable performance.

What you can expect

ENERGY-EFFICIENCY

Our dual-pane insulated glass helps save on heating and cooling costs while enhancing home comfort.

- In cool weather, it provides outstanding thermal performance to eliminate cold spots near windows.
- In warm weather, insulated glass reduces solar heat gain and minimizes interior glare.

CONVENIENCE AND STYLE

- Beveled exterior profile creates a clean, timeless aesthetic
- Surface-mounted tilt latches and forced-entry-resistant locks provide a stronger, safer seal
- Full-length lift rail for easy opening and closing
- Tilt-in bottom sash for easy cleaning
- Optional window operating control device for enhanced safety

Engineered to perform

- Welded, multi-chamber frame and sash
- Heavy-duty weatherstripping
- Available frame styles: mounting fin, flange, finless
- 2 ⅞" frame depth
- Available with brickmould accessory and integral J-channel
- Wood extension jambs available for 4 $^{9}/_{16}$" and 6 $^{9}/_{16}$"

Min and max sizing

WIDTH		HEIGHT	
MIN	MAX	MIN	MAX
13"	48"	24"	96"
48"	52"	24"	84"
CONTINUOUS HEAD & SILL (CHS) MAX			
Twin (Each Window)	47 ¾"	84"	
Twin (Overall Unit)	95 ⅝"	84"	
Triple (Each Window)	36"	84"	
Triple (Overall Unit)	108 ¼"	84"	

Available in 1/4" increments. DP upgrade required for any unit greater than 84" tall.
CHS available on XX, XO, OX, XX, and XOX configurations.

Energy efficient glass

Optional tempered glass adds additional strength and obscure or rain glass allows light in while protecting privacy.

GLAZING TYPE	U-VALUE	SHGC	STC
Low-E glass	0.33	0.28	27
Low-E glass with grids	0.33	0.26	27
Argon and Low-E glass	0.30	0.28	27
Argon and Low-E glass with grids	0.30	0.26	27
HP Low-E glass	0.33	0.21	27
HP Low-E glass with grids	0.33	0.19	27
Argon and HP Low-E glass	0.30	0.21	27
Argon and HP Low-E glass with grids	0.30	0.19	27
Argon and LoĒ³-340 glass	0.30	0.15	27
Argon and LoĒ³-340 glass with grids	0.30	0.13	27

Note: all values based on standard 3/4" dual-pane insulated glass unit unless noted otherwise

ENERGY STAR PARTNER

NFRC CERTIFIED

FGIA Fenestration & Glazing Industry Alliance

Create a customized look

Enhance your home's spaces with a variety finish options and grid configurations.

COLOR OPTIONS

EXTERIOR	INTERIOR
White EXTRUSION	White EXTRUSION

GRID TYPES

Grids-Between-the-Glass
Flat

Sculptured

Simulated Divided Lite

Simulated Meeting Rail